

COPIER

Copying process:	4-drum dry electrostatic transfer system with internal transfer belt	
Copy speed:	MP C6000: B/W: 60 copies per minute Full colour: 55 copies per minute MP C7500: B/W: 75 copies per minute Full colour: 70 copies per minute	
Resolution:	600 dpi	
Multiple copy:	Up to 9,999	
Warm-up time:	Less than 75 seconds	
First output speed:	MP C6000: B/W: Less than 5.7 seconds Full colour: Less than 7.5 seconds MP C7500: B/W: Less than 4.9 seconds Full colour: Less than 6.4 seconds	
Zoom:	25 - 400% (in 1% steps)	
Memory:	Standard: 1,536 MB + 320 GB Hard Disk Drive (shared with printer function)	
Paper input capacity:	Standard: 2 x 1,100-sheet tray 2 x 550-sheet trays 1 x 100-sheet bypass tray Maximum: 7,400 sheets	
Paper output capacity:	500 sheets	
Paper size:	A5 - A3+	
Paper weight:	Paper trays: 52 - 216 g/m ² Bypass tray/wide LCT tray: 52 - 300 g/m ² Duplex tray: 64 - 163 g/m ²	
Dimensions (W x D x H):	750 x 850 x 1,230 mm	
Weight:	Less than 298 kg	
Power source:	220 - 240 V, 50/60 Hz	
Power consumption:	Operation: Maximum 2.4 kW Energy saver mode: MP C6000: Less than 236 W MP C7500: Less than 294 W	

FAX (OPTION)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3, T.37, T.38
Modem speed:	Maximum 33.6 Kbps
Resolution:	200 x 100/200 dpi
Compression method:	MH, MR, MMR, JBIG
Scanning speed:	0.5 second (200 x 100 dpi, A4, SEF)
Memory capacity:	4 MB
Memory backup:	Yes

OTHER OPTIONS

• 2,000-sheet large capacity tray (A5 - A3+) (RT4000), 4,000-sheet large capacity tray (A4) (RT43), A3 tray unit (Type 2105), 3,000-sheet finisher with 100-sheet stapler (SR5000), 3,000-sheet finisher with 50-sheet stapler (SR4010), 2,000-sheet booklet finisher (SR4020), Jogger unit for finisher SR4010/SR4020, 9-bin mailbox (CS391) for finisher R4010/SR4020, 2-source cover interposer for finisher SR5000, Cover interposer for finisher SR4010/4020, Several punch kits, Professional booklet maker BK5010, Z-folder, GBC StreamPunch™ III, Copy tray, Tab sheet unit, Fax unit, SAF memory, 2nd Super G3 port, Data Overwrite Security Unit, Copy Data Security Unit, HDD encryption unit, File Format Converter, Copy Connect kit, Browser unit, VM card, Key counter bracket, Counter interface unit, Adobe® PostScript® 3™, Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/g), Bluetooth, Gigabit Ethernet, Professional software solutions

COLOR CONTROLLER E-7100/E-8100

CPU:	E-7100: Intel Celeron M440 1.86 GHz E-8100: Intel Core 2 Duo 2.13 GHz
Memory:	Standard: 1 GB Hard Disk Drive: E-7100: SATA 80 GB E-8100: SATA 160 GB
Print speed:	MP C6000: B/W: 60 prints per minute Full colour: 55 prints per minute MP C7500: B/W: 75 prints per minute Full colour: 70 prints per minute
Printer language:	Standard: PCL5c, PCL6, Adobe® PostScript® 3™
Resolution:	600 dpi (print & scan)
Interface:	Ethernet 10 base-T/100 base-TX/1000 base-T USB 2.0 (for USB Media Print)
Network protocol:	TCP/IP, AppleTalk, SMB
Fonts:	Adobe® PostScript® 3™: 138 fonts PCL: 80 Agfa fonts
Utility software:	Standard: EFI Command WorkStation™ Windows® Edition v4.6 EFI Command WorkStation™ Macintosh Edition v1.5 EFI Fiery ColorWise Pro Tools™ Fiery Remote Scan™ (application, TWAIN plug-in) Fiery Printer Delete Utility Fiery WebTools™ Auto Trapping (optional for E-7100) Spot-On (optional for E-7100) EFI Hot Folders (optional for E-7100) EFI Impose (optional for E-7100) Paper Catalogue (E-8100) Option: EFI Color Profiler Graphic Arts Package Premium Edition (E-8100) Graphic Arts Package (E-8100) EFI Compose (E-8100)

The E-7100 is currently available. The E-8100 will be available towards the end of 2008.

For availability of models, optional apparatus and software, please consult your local Ricoh supplier.

For detailed specifications of the Aficio™ MP C6000/MP C7500, please visit www.ricoh.eu or consult the individual product brochures.



ISO9001: 2000 certified
ISO14001 certified

Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.

Ricoh believes in conserving the earth's precious natural resources. This brochure is printed on environmentally friendly paper: 50% recycled fibres, 50% chlorine free bleached pulp.

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2008 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

www.ricoh.eu